

Comfort Grip VB Hose Connector







Complete your Aquor system with the Comfort Grip VB Hose Connector for backflow protection. Downturned angle for ease of use and integrated ball valve for flow control. Use with or without a garden hose. ASSE 1019 and CSA B125 certified.


- Angled for easier leverage
- Standard 3/4" garden hose thread
- Built-in ball valve for flow control and vacuum breaker for backflow protection
- ASSE 1019 & CSA B125 certified

Compatibility	All Aquor hydrants & valves
Color	Slate Gray
Outlet	3/4" GHT (m)
Backflow Protection	Yes
Operating Temperature	33-140 °F
Operating Water Pressure	25-125 PSI
Flow Rate	6.8 GPM @ 52 PSI
Connector Material	Acetal Resin Polymer & EPDM Rubber
O-Ring Material	Fluorocarbon Rubber
Warranty	5 Years
Certifications	ASSE 1019 & CSA B125
SKU	CN-VB3




Comfort Grip VB Hose Connector


Connecting to your Aquor Hydrant



First thread your hose connector onto any hose.



To connect, align the 3 grooves on the connector with the nibs on the hydrant. Gently push in, then twist clockwise.



Once you connect, the valve opens and water flow starts instantly.



Disconnect and depressurize your hose before storing.

