



Enjoy convenient year-round tempered water access with the Aquor® Hot+Cold Hydrant. Single dial to control temperature, hose connector to control the flow. The Hot+Cold Hydrant has everything you need to do more outdoors.

- Recommended for new construction
- Temperature control knob designed for all ages and abilities
- Durable ceramic mixing cartridge
- 316L stainless steel and 100% non-toxic materials
- Automatic, superior freeze protection
- Complete front serviceability if needed

<b>In the Box</b>	Hydrant with plug cover, x4 #10 wedge mounting screws, x2 M5 x 10mm hydrant mounting screws, CN-VB3 hose connector, CN-VB2 hose connector, mounting template
<b>Entry Hole</b>	3.5"
<b>Backflow Protection</b>	External vacuum breaker in hose connector
<b>Inlet</b>	1/2" PEX F1960
<b>Outlet</b>	3/4" GHT (m)
<b>Operating Temperature</b>	33 -140 °F
<b>Operating Water Pressure</b>	25-125 PSI
<b>Flow Rate</b>	6.6 GPM @ 50 PSI
<b>Plumbing Compatibility</b>	PEX A
<b>Hydrant Material</b>	316L Stainless Steel, Polymers
<b>Mixing Cartridge</b>	CC-HC1
<b>Connector Material</b>	Acetal Resin Polymer
<b>O-Ring Material</b>	Fluorocarbon Rubber
<b>Cover Material</b>	EPDM Rubber
<b>Certifications</b>	ASSE 1019C, ASME A112.18.1, CSA B125.1
<b>Warranty</b>	Limited LIFETIME all stainless steel parts, 5 years polymer parts



